

Arga Chassis Grease

Multipurpose Water Resistant Automotive Grease

PRODUCT DESCRIPTION

Arga Chassis Grease, is a green colored multi purpose grease formulated with quality base oils, calcium soap and cohesion-improver components.

APPLICATIONS

- It is suitable to use in low speed plain bearings and automotive chassis applications up to 70°C.

CHARACTERISTICS

- Excellent resistance against water washout due to cohesion-improver components in its formulation.
- Its fibery and water-resistant structure provides active wear and corrosion protection.

TYPICAL PROPERTIES

NLGI		3
Colour		Dark Green
Soap Type		Calcium
DIN Classification	DIN 51502	K 3 K-20
ISO Classification	ISO 6743-9	L-XBCEA-3
Worked Penetration, 0.1 mm (25°C, 60 Stroke)	ASTM D 217	220-250
Dropping Point, °C,	ASTM D 566	>100
Operating Temperature, °C		70 max

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.