

Arga Super EPX 2

Heavy Duty Automotive Grease with Solid Lubricants

PRODUCT DESCRIPTION

Arga Super EPX 2, is a multi purpose excellent performance lithium based automotive grease containing molybdenum disulphide (MoS₂). It has high load carrying capacity and excellent wear protection feature due to extreme pressure (EP) additive. It gives an outstanding performance even under high loads due to low leakage feature, water wash-out resistance and high oxidation stability. It is recommended for lubrication of camshaft, slideway and other moving machine components have longer re-greasing intervals and exposed to limited, impact or vibrating loads.

APPLICATIONS

- It is suitable for components operating under low speed, high and impact load conditions in construction equipment, heavy and light commercial vehicles and passenger vehicles. It is recommended for general lubrication of construction equipment.

CHARACTERISTICS

- Provides excellent protection under vibrating and impact loads.
- Its high water wash-out and steam resistance provides longer re-greasing intervals, so reduces greasing cost.
- Its high rust and corrosion protection extends equipments service life.

TYPICAL PROPERTIES

NLGI		2
Colour		Black
Soap Type		Lithium
DIN Classification	DIN 51502	KPF 2K-30
ISO Classification	ISO 6743-9	L-XCCEB-2
Worked Penetration, 0,1mm (25°C, 60 strokes)	ASTM D 217	265-295
Base Oil Viscosity @40°C, mm ² /s	ASTM D 445	180,0
Base Oil Viscosity @100°C, mm ² /s	ASTM D 445	16,0
Dropping Point, °C	ASTM D 566	>190
Operating Temperature, °C		-30 to 130
4-Ball Weld Load, N	ASTM D 2596	>3200

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.