

ATF CVT

Synthetic Continuously Variable Transmission (CVT) Fluid



PRODUCT DESCRIPTION

ATF CVT, is a synthetic automatic transmission fluid based on special technology base oils and additives, formulated for continuously variable transmission of passenger cars.

APPLICATIONS

- It is suitable to use in continuous variable transmission (CVT) of passenger cars.

CHARACTERISTICS

- Provides effective wear protection even at very low temperatures and under high load, so extends the lifetime of the automatic transmission and lowers maintenance costs.
- Minimizes friction and dissipates heat, so provides smooth gear shifting over a wide operating temperature range.
- Outstanding oxidation and shear stability offers reliable performance during long drain interval.
- Excellent performance in cold and very high temperature operation.

PERFORMANCES

- AUDI MULTI TRONIC
- BMW MINI COOPER EZL 799/799A
- DODGE/JEEP/CHRYSLER NS-2 / CVT+4
- CVT FLUID J1
- CVT FLUID DFE
- DAIHATSU AMMIX CVT FLUID DC
- FORD CVT23
- HONDA HMMF/HCF-2/Z-1
- MAZDA JWS 3320
- MITSUBISHI CVTF-J1/J4/J4+
- MMC DIAQUEES ATF SP-III
- NISSAN NS-1/NS-2/NS-3
- SUBARU İCVT/FG/ECVT/NS2
- SUZUKI CVTF TC/TC 3320/NS2
- SUZUKI CVT FLUID GREEN 1 AND 2/1V
- TOYOTA CVT FLUID TC / FE
- VW/AUDI TL 521 16 (G 052 516)
- VW/AUDI TL 521 80 (G 052 180 A2)

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,849
Viscosity@ 40°C, mm ² /s	ASTM D 445	35,8
Viscosity@100°C, mm ² /s	ASTM D 445	7,45
Viscosity Index	ASTM D 2270	181
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-48

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.