



FMY

TECHNICAL DATA SHEET

FMY COMPLEX GREASE 2

Ford Cargo Wheel Bearing Grease

PRODUCT DESCRIPTION

FMY Complex Grease 2 is a long-life grease which is specially developed to be used in the wheel bearings (without disc brake system) of Ford Cargo trucks. Its lithium complex soap and extreme pressure (EP) additives offers outstanding performance in the wheel bearings operating under high temperatures and heavy loads, so provides a long life use.

CHARACTERISTICS

- Suitable for heavy operating conditions.
- Resists up to 180 °C.
- Excellent resistance to corrosion and oxidation allows long life use.
- Does not contain heavy metals.
- High mechanical stability.

APPLICATIONS

- It is suitable to be used in the wheel bearings (without disk brake system) of Ford Cargo trucks.

FORD APPROVAL

FORD WSD-M1C228-A

PACKAGING AND PART NUMBERS

16 KG	WSD-M1C228-16L
180 KG	WSD-M1C228-180L



FMY

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

NLGI		2
Color		Amber
Thickening Agent		Lithium Complex
Base Oil Viscosity @40°C, mm ² /s	ASTM D 445	160
Base Oil Viscosity @100°C, mm ² /s	ASTM D 445	15.5
Dropping point °C,	ASTM D 566	300
Worked penetration, 0,1 mm (@25°C, 60 strokes)	ASTM D 217	275
Operating Temperature Range, °C		-20°C to 180°C
4-Ball Weld Load, kg	ASTM D 2596	300
Timken Test OK Load, Lbs	ASTM D 2506	50

HEALTH and SAFETY RECOMMENDATIONS

Waste products must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used products may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.