

Fullife 5W-30

Optimum Lubrication with Synthetic Technology



PRODUCT DESCRIPTION

Fullife 5W-30 is a synthetic engine oil developed with uses advanced additive technology to meet the needs of passenger cars and light commercial vehicles' engines. It is developed with a recipe containing special additive technology to prevent soot formation and minimize wear and tear inside the engine.

APPLICATIONS

It is suitable for use in

- Gasoline or diesel engines of passenger vehicles or light commercial vehicles, gasoline engines of hybrid vehicles.
- Japanese vehicles that recommended ILSAC GF-6 specification.
- Engines of OPEL brand vehicles where GM dexos1™ gen 2 performance is required.

CHARACTERISTICS

- Its high oxidation stability maintains its protection until the next oil change.
- Its high viscosity index provides superior engine performance for all seasons.
- Its active cleaning feature controls the deposit and sludge formation at high temperatures, so keeps the engine parts clean.
- It reduces oil consumption due to its low volatility; so, helps decrease hydrocarbon pollution.

PERFORMANCES

- API SP-RC
- GM dexos1™ gen 2
- ILSAC GF-6

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,852
Viscosity@ 40°C, mm ² /s	ASTM D 445	64,2
Viscosity@100°C, mm ² /s	ASTM D 445	11,1
Viscosity Index	ASTM D 2270	167
Flash Point, °C	ASTM D 92	230
Pour Point, °C	ASTM D 97	-39
TBN, mgKOH/g	ASTM D 2896	8,3

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.