

Fullmoto 4T Outboard FC-W 25W-50 4-Stroke Outboard Synthetic Based Engine Oil

PRODUCT DESCRIPTION

Fullmoto 4T Outboard FC-W 25W50, is a 4-stroke outboard engine oil which is formulated with synthetic based oils and advanced additive technology.

APPLICATIONS

- It is designed for high performance 4-stroke outboard engines.
- It is suitable to use in Mercury Verado 1.7L and 2.6L engines.
- It can be use on engine Where NMMA FC-W approval is requested.

CHARACTERISTICS

- Its synthetic based formula provides high performance within a wide temperature range.
- Its detergent and dispersant additives keep the engine clean.
- It provides high protection against corrosion, oxidation, rust, wear and prevents formation of foam.

APPROVALS

- NMMA FC-W

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,877
Viscosity@ 40°C, mm ² /s	ASTM D 445	188,9
Viscosity@100°C, mm ² /s	ASTM D 445	19,6
Viscosity Index	ASTM D 2270	119
Flash Point, °C	ASTM D 92	259
Pour Point, °C	ASTM D 97	-33

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.