

Fullpro HT MSPS 10W-40

Approved Performance with Mid SAPS Technology



PRODUCT DESCRIPTION

Fullpro HT MSPS 10W-40, is a diesel engine oil which provides ultra high performance in low emission diesel engines of heavy commercial vehicles. It helps to extend the engine service life. The combination of state of the art additive technology with special base oils enables long oil drain interval. It improves efficiency of exhaust gas emission systems such as Diesel Particulate Filter (DPF), Diesel Oxidation Catalyst (DOC) and Exhaust Gas Recirculation (EGR).

APPLICATIONS

- It is suitable to use in low emission diesel engines of modern technology heavy commercial vehicles fitted with DPF, DOC, and EGR.
- It is suitable for use in diesel engines of vehicles operating in construction, mining, agriculture, and transportation sectors.

CHARACTERISTICS

- Its special formula improves efficiency of exhaust after treatment systems such as DPF, DOC and EGR.
- Its advanced additive technology provides excellent wear protection in the engine under extreme operating conditions.
- Its excellent fluidity during cold weather conditions protects the engine against wear by providing quick lubrication of engine parts during the first start.
- Its superior soot handling keeps the engine clean, provides ultra high engine performance, and reduces maintenance costs.

APPROVALS

- CNH MAT 3521 / 3571

PERFORMANCES

- ACEA E9
- API CK-4/SN
- CAT ECF-3
- CNH MAT 3571
- CUMMINS CES 20086
- DDC 93K222
- DEUTZ DQC III-18 LA
- DTFR 15C100 (ex MB APPROVAL 228.31)
- FORD WSS-M2C171-F1
- MACK EO-S 4.5
- MAN M 3775
- MB APPROVAL 228.31
- MTU TYPE 2.1
- RENAULT RLD-4
- VOLVO VDS 4.5

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,868
Viscosity@ 40°C, mm ² /s	ASTM D 445	103,39
Viscosity@100°C, mm ² /s	ASTM D 445	15,09
Viscosity Index	ASTM D 2270	153
Flash Point, °C	ASTM D 92	230
Pour Point, °C	ASTM D 97	-33
TBN, mgKOH/g	ASTM D 2896	8,1
Sulfated Ash, wt%	ASTM D 874	1,0

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.