

Fullpro HT SYN LD 5W-30

High Performance Full Synthetic Diesel Engine Oil



PRODUCT DESCRIPTION

Fullpro HT SYN LD 5W-30, is an high performance full synthetic engine oil that is specially developed for the first and service filling of new generation low emission Euro VI engines of road or construction series of Ford Trucks.

APPLICATIONS

- It is suitable to use in the first and service filling of road or construction series of Ford Trucks or F-Max tractors produced till the end of 2022 only.
- It is suitable to use in Euro V and Euro VI diesel engines of other makes fitted with exhaust gas after treatment systems such as DPF, EGR, and SCR.

CHARACTERISTICS

- The latest additive technology improves the efficiency of exhaust gas after treatment systems such as DPF (Diesel Particulate Filter), EGR (Exhaust Gas Recirculation), and SCR (Selective Catalytic Reduction) and prolongs the life of these systems.
- Its active cleaning feature offers residue and sludge control, so keeps engine parts clean.
- Its superior thermal and oxidation stability maintains its performance during the extended oil drain interval.
- It offers fuel economy.
- It provides excellent wear protection during cold start-up due to its improved low temperature characteristics.

PERFORMANCES

- ACEA E7/E6
- DEUTZ DQCIV-10LA
- DTFR 15C110 (ex MB-APPROVAL 228.51)
- FORD WSS-M2C213-A1
- MACK EO-N
- MTU 3.1
- RENAULT RLD-2
- SCANIA LDF-4
- VOLVO VDS-3

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,853
Viscosity@ 40°C, mm ² /s	ASTM D 445	68,6
Viscosity@100°C, mm ² /s	ASTM D 445	11,4
Viscosity Index	ASTM D 2270	160
Flash Point, °C	ASTM D 92	228
Pour Point, °C	ASTM D 97	-42
TBN, mgKOH/g	ASTM D 2896	10,1

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.