

Fulltrac Fluid X 10W-30

General Purpose Universal Tractor Transmission Oil (UTTO) for Tractors and Agricultural Machines

PRODUCT DESCRIPTION

Fulltrac Fluid X 10W-30, is a multi purpose (UTTO) transmission oil for automatic or manual transmissions, hydraulic, axle, wet brake systems, final drives or PTO (Power Take Off) of tractor or agricultural machines. Quality base oils and anti-friction additives in its formulation provides high and quite performance in transmitting power.

APPLICATIONS

- It is suitable to use in manual transmissions, hydraulic systems, axles, wet brake systems, final drives or PTO of tractor or agricultural machines.

CHARACTERISTICS

- It provides effective protection against high velocity/low torque or low velocity/high torque wear.
- Its perfect viscosity-temperature characteristic offers reliable performance at low temperatures.
- Its anti-friction additives allow wet brake system to operate efficiently and silently.
- Its specially developed formula provides long service life by controlling rust, corrosion and foam formation.
- Its high thermal and oxidation stability prevents sludge formation and increases efficiency.

PERFORMANCES

- ALLISON C-4
- API GL-4
- CASE MS 1210
- CNH MAT 3525
- FORD ESN-M2C86-B/C/ESN-M2C134-D
- JOHN DEERE JDM J20D/C
- KUBOTA UDT FLUID
- MASSEY FERGUSON CMS M 1145/1143/1141/1135
- VOLVO CE WB101
- ZF TE-ML 17E/06K/05F/03E

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,877
Viscosity@ 40°C, mm ² /s	ASTM D 445	58,3
Viscosity@100°C, mm ² /s	ASTM D 445	9,7
Viscosity Index	ASTM D 2270	150
Flash Point, °C	ASTM D 92	219
Pour Point, °C	ASTM D 97	-36

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.