



TECHNICAL DATA SHEET

ECONOMIZER

PRODUCT DESCRIPTION

Economizer improves engine oil viscosity index by the high quality additives in its content.

CHARACTERISTIC/ADVANTAGES

- Prevents excessive oil consumption due to wear.
- Helps to reduce fuel consumption.
- Reduces exhaust smoke caused by excessive oil consumption.
- Restores compression and improves engine performance.
- Reduces engine noise and wear by forming stable oil film layer between cylinder and piston.

APPLICATION

- Recommended to be used in Diesel and Gasoline -powered vehicles, in order to prevent increased fuel / oil consumption and loud engine operation resulting especially from the wear on the engine parts of the old vehicles.

USAGE

- Preferably, add 1 (400 ml) Economizer to 4-6 liters of engine oil through oil plug while the engine is at operating temperature together with new oil change. Once added, run the engine at idle for 10 minutes.

TYPICAL PROPERTIES

Viscosity @100°C, cSt	ASTM D 445	363
Flash Point, °C	ASTM D 92	216



TECHNICAL DATA SHEET

HEALTH AND SAFETY RECOMMENDATIONS

It is flammable, so must be kept away from fire and sparks. Eye contact should be avoided. In case of eye contact, wash with plenty of water. If contact with skin, wash the area immediately with plenty of water and soap. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.