



TECHNICAL DATA SHEET

GASOLINE TREATMENT

PRODUCT DESCRIPTION

Gasoline Treatment is a fuel additive that is specially developed for gasoline engines to improve engine performance by improving combustion.

CHARACTERISTIC/ADVANTAGES

- Prevents formation of soot and carbon in valves and combustion chamber.
- Cleans valves and cylinder parts in contact with fuel.
- Improves engine performance.
- Improved drivability: smoother accelerations and idle: reduces tendency to stall.
- Controls corrosion, thus extends engine life.

APPLICATION

- Recommended for use in the fuel systems of gasoline vehicles in order to ensure smooth and high performance operation of the engine.

USAGE

- Mix 1 (200 ml) Gasoline Additive with 40-60 liters of fuel.
- When used in every refueling, helps keep your engine well maintained and clean.
- For the optimum results, first Gasoline Additive and then the fuel should be filled into the fuel tank.



TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Specific Gravity @15°C, kg/L	ASTM D 4052	0,772
Flash Point, °C	ASTM D 92	54

HEALTH AND SAFETY RECOMMENDATIONS

It is flammable, so must be kept away from fire and sparks. Eye contact should be avoided. In case of eye contact, wash with plenty of water. If contact with skin, wash the area immediately with plenty of water and soap. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.