

Super Antifreeze All Season Antifreeze

PRODUCT DESCRIPTION

Super Antifreeze, is a superior quality ethylene glycol based coolant formulated with special additives for cooling systems of all gasoline and diesel engines. It prevents radiator water from freezing in cold climates and prevents radiator water from boiling due to its special formulation.

APPLICATIONS

- It is suitable to use in engine coolant systems of passenger vehicles, light commercial and heavy commercial vehicles, agricultural and construction equipments all season.

CHARACTERISTICS

- It is compatible with cooling system components and sealing elements.
- It protects the cooling system against oxidation and corrosion. It prevents formation of electrolysis, thus enables cooling system has a long service life and high performance.
- It should be used by mixing with water . The antifreeze ratio in mixture should not be less than 33% and more than 67%.It should not be used with extremely hard water, sea water, salty water and waste water.

PERFORMANCES

- BS 6580:1992
- TS 3582

TYPICAL PROPERTIES

Colour		Blue
Density@20°C, g/ml	ASTM D 4052	1,120
Pour Point, °C	ASTM D 1177	
%50 Opet Super Antifreeze+%50 Water		-37
%33 Opet Super Antifreeze+%67 Water		-17
Boiling Point, °C	ASTM D 1120	163
pH (%50 Water Mixture)	ASTM D 1287	8,6

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.