



Product specifications



Consumer range

ENGINE STOP LEAK

for petrol or diesel engines

Wynn's Engine Stop Leak is a special blend of chemicals formulated to stop engine oil leaks and drips that can result from the drying out and shrinking of engine neoprene, rubber seals and O-rings.

Properties

- ✓ Prevents and stops engine oil leaks without demounting.
- ✓ Restores the elasticity of rubber and neoprene oil seal rings and O-rings.
- ✓ Lubricates and maintains engine seals in good condition.
- ✓ Will have no effect on the viscosity or performance of engine oil.
- ✓ Is compatible with all mineral and synthetic, single- and multigrade oils.
- ✓ Does not harm catalytic converters.

Applications

- ✓ Recommended for all petrol, LPG and diesel engines of vehicles and stationary equipment.
- ✓ Works on all rubber and neoprene seal rings in the engine.
- ✓ Effective for excessive leakages at the rubber or neoprene valve stem seals.

Technical data

Appearance	: yellow-brown oily liquid
Density at 15°C	: 0,905 kg/dm ³
Viscosity at 40°C	: 19,4 mm ² /s
Viscosity at 100°C	: 3,4 mm ² /s
Flash Point	: > 150°C
Pour Point	: <-25°C

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
 Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.eu

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.



Product specifications

Directions

- ✓ Add entire contents of one can to the engine oil. Run engine to circulate. Drive vehicle normally.
- ✓ One can of 325 ml treats up to 6 litres of engine oil.
- ✓ Allow up to 200 miles/300 km for Engine Stop Leak to be fully effective.
- ✓ If no improvement occurs, a mechanical deficiency is likely.
- ✓ Application does not influence oil change intervals.

Packaging

PN 50660 – 12x325 ml – FR/DE/NL/ES/PT

PN 50664 – 24x325 ml – EN

PN 50672 – 12x325 ml – PL/HU/RU/EL

Note

Wynn's Engine Stop Leak cannot correct mechanical defects or damaged seals.

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
Tel: 32-3-766.60.20 - Fax: 32-3.778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.eu

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.