



Product specifications



Professional range

Viscotene

Wynn's Viscotene is a strongly adhesive and high viscosity synthetic lubricant.

Properties

- ✓ Exceptionally adhesive to surfaces.
- ✓ Exceptionally water-repellent and water-resistant.
- ✓ Protects parts, hard to be lubricated.
- ✓ Reduces and dampens noise of mechanisms.
- ✓ Resists steam washout, solvents and acids.
- ✓ Reduces wear and corrosion.
- ✓ Outstanding viscosity characteristics over a wide temperature range.

Applications

- ✓ Mechanisms exposed to moisture, warm or cold water, detergents, acids, steam.
- ✓ Equipment for which conventional lubricants drip or leak away.
- ✓ Functions as dampener of vibrations, noise and wear. Compensates for variations in clearance and pressure.
- ✓ In all cases where conventional oils and greases are difficult to apply.
- ✓ Electrical wiring harnesses (motorcycles, cars, trucks).
- ✓ For cables, mechanical parts, springs, ... on cars, trucks, tractors, in road construction, mines, agriculture, marine applications, in paper, metallurgic and glass industry.
- ✓ For fast moving chains (e.g. motorbikes, go-carts, etc.).

Technical data

Appearance	: yellow viscous
Density at 15°C	: 0,943 (of gas free product)
Viscosity at 100°C	: 850 - 950 mm ² /s (of gas free product)
Flash Point	: 195°C (of gas free product)
Operating temperature range	: -20 to +130°C

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
 Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.eu

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.



Product specifications

Propellant gas aerosol : propane/butane

Directions

- ✓ Make surfaces to be lubricated clean and dry, using a product such as Wynn's Brake and Clutch Cleaner.
- ✓ Apply the product by spray can.
- ✓ Allow solvent to sufficiently evaporate, prior to further manipulation of the material. Only spray on elements to be lubricated or protected.

Packaging

PN 80179 – 12x500 ml aerosol – EN/FR/DE/ES/IT/NL/DA/NO/SV/FI

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.eu

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.